

Architectural floor plan of a building, oriented horizontally. The plan is defined by a grid system with vertical lines labeled 22 through 29 and horizontal lines labeled A through F. Dimensions are provided for various sections:

- Horizontal dimensions (top): 7500 (22-23), 6500 (23-24), 6500 (24-25), 44500 (25-26), 6500 (26-27), 6500 (27-28), 4500 (28-29), and 525 (29-29.5).
- Vertical dimensions (left): 570 (A-B), 28540 (B-C), 500 (C-D), 7000 (D-E), and 570 (E-F).
- Vertical dimensions (right): 300 (F-29.5), 8040 (29.5-28), 6500 (28-27), and 4650 (27-26).

Key features include:

- A staircase located between grid lines 22 and 23, between grid lines C and D, at an elevation of ± 84.250 .
- A staircase located between grid lines 28 and 29, between grid lines C and D, at an elevation of ± 84.250 .
- A staircase located between grid lines 28 and 29, between grid lines E and F, at an elevation of ± 92.450 .
- A staircase located between grid lines 26 and 27, between grid lines E and F, at an elevation of ± 92.450 .
- A central corridor running horizontally between grid lines C and D.
- A central corridor running vertically between grid lines E and F.
- A north arrow pointing towards the top right corner.

[illegible]